

Template for Brandable VESA Mount Security Floor Stand

COMPULOCKS

Design Guidelines for the Brandable Panel

To ensure your artwork prints perfectly, please follow the guidelines below:

- Keep your artwork inside the grey area on the "Your Design Here" layer.
- Work in CMYK color mode and save your file accordingly.
- Convert all text to outlines (select all, go to main menu, choose Type > Create Outlines).
- Use vector graphics when possible; raster images must be 300 ppi or higher.
- Save your final file as PDF/X-1a for best compatibility.



Safe Area - 150mm (5.9in) x 840mm (33.07in)

This is the space where all important parts of your design (like logos, text, or key images) should go. Anything placed outside of this area might get cut off during printing or installation



Bleed Area

Extend any backgrounds, colors, or images beyond the safe area and out to the bleed line.

This prevents unwanted white edges in case of slight cutting shifts.

Tip: Bleed usually extends 0.125" (3mm) beyond each edge.



Panel Size (Full Area) - 160mm (6.3in) x 930mm (36.61in)

This is the full size of the printable panel, including the bleed and safe area. Your file should be set up to this size, even though only the safe area is guaranteed to be fully visible once installed.

Graphics panel thickness:

5mm $\pm$ 5% max
(0.2in $\pm$ 5% max)

Panel material examples:

Backlit: clear acrylic/polycarbonate*
Standard: foam board, foamed PVC panel*

**Examples only, consult chosen printing services for recommended material and print methods.*

Need help?

Email us at online@maclocks.com or chat with our team at www.maclocks.com

